

Dakota Compact

Aspirapolvere - Aspiraliquidi
Wet and Dry Vacuum Cleaners



IPC Soteco

IPC Integrated Professional Cleaning

Dakota Compact



MODELLO MODEL	Motore bistadio Two stage motor	Volt	Depress. col acqua Waterlift	Aria aspirata Air flow	Capacità totale fusto Total tank capacity
	W		mm	m ³ /h	l
101 SPOT	1000 max thru flow	220-240	2280	170	35
103 SPOT	1150 max thru flow	220-240	2470	180	35
115 SPOT	1200 max by pass	220-240	2470	210	35
Access. standard/Standard Accessories Ø36: 1685 (1685G) - 6240 (2pcs) - 6158 - 616 - 617 - 632 - 4 (Mod.115 + 2720 - Optional 2852 - 2855)					
315 SPOT	1200 max by pass	220-240	2470	210	50
303 SPOT	1400 max by pass	220-240	2500	215	50
315 M - 315 B/T	1200 max by pass	220-240	2470	210	90-114 B/T
303 M - 303 B/T	1400 max by pass	220-240	2500	215	90-114 B/T
Accessori standard/Standard Accessories Ø38: 6295 - 6388 - 3 - 8 - 6387 (2pcs) - 6389 - 6384 - 6385 Optional 2852 - 2855 - 6386					
415 M - 415 B/T	1200 max by pass	220-240	2470	210	90-114 B/T
403 M - 403 B/T	1400 max by pass	220-240	2500	215	90-114 B/T
429 M - 429 B/T	2400 max by pass	220-240	2470	420	90-114 B/T
423 M - 423 B/T	2600 max by pass	220-240	2500	430	90-114 B/T
440 M - 440 B/T	3300 max by pass	220-240	2470	630	90-114 B/T
433 M - 433 B/T	3500 max by pass	220-240	2500	645	90-114 B/T
Accessori standard/Standard Accessories Ø38: 6295 - 6388 - 3 - 8 - 6387(2pcs) - 6389 - 6384 - 6385 Optional 2852-2855 - 6386-41-42-3200					

I dati relativi a depressione e aria aspirata si riferiscono ai singoli motori - Information about waterlift and airflow refers to single motors
 Dati, descrizioni e illustrazioni sono forniti a titolo indicativo: la ditta si riserva di modificarli senza preavviso - Specifications, descriptions and pictures are supplied as indicative: IPC Soteco reserves modifying them without notice

Accessori Ø36 / Accessories Ø36 Accessori Ø38 / Accessories Ø38 Accessori / Optional / Accessories

